

RESET your thinking, a revolution has arrived in roof window installation.

4-GLAZED roof window IGX F1
with RUBBER FLASHING



The IGX F1 RESET (fixed, 78x98cm) consists of the following:

- 4-glazed window IGX F1
- integrated rubber flashing RESET
- integrated fitted permeable under felt collar AKP.

The elements are integrated which speeds up the installation!




okpol.pl/reset




## **IGX F1 RESET**

4 - GLAZED ROOF WINDOW WITH RUBBER FLASHING



# UP TO 40% MORE LIGHT

78x98 roof window gives you up to 40% more glazing compared to other windows with the same frame size.



#### WARM QUADRUPLE GLAZING UNIT

- Laminated inner pane with foils for safety (class P2A)
- 6mm toughened outer pane for strength
- Structure of glazing unit 6H/18/4TH/20/44.2T
- The heat transfer coefficient Ug = 0,5 W/m<sup>2</sup>K



#### SUPER ENERGY-SAVING WINDOW

The heat transfer coefficient of the window Uw = 0,79 W/m<sup>2</sup>K (for the reference sample according to norm EN ISO 10077-2 / EN ISO 10211).



PERMEABLE UNDERFELT **COLLAR AKP INCLUDED** 



## **PVC PROFILE DOESN'T** REQUIRE MAINTENANCE

filled with polyurethane foam, resistant to weather conditions



**LOWEST ROOF PITCH INSTALLATION** 50-900



#### **INNOVATIVE DESIGN**

reduced number of screws and the amount of aluminum









**RUBBER FLASHING (EPDM)** for roof windows



15 min THE QUICKEST MOUNTING (IGX + RESET)



INTEGRATED FLASHING **ALLOWS INSTALLATION FOR MANY DIFFERENT ROOFING MATERIALS** 



5°-90° **LOWER MOUNTING ANGLE** (IGX + RESET)



## **INSTALL IN A COMBINATION FOR FREE**

use multiple windows with integrated flashings for combinations of your choice.



## **HIGHEST RESISTANCE**

The flashing is resistant to:

- stretching mechanical damage
- weather conditions (UV radiation)

www.okpol.com

